


**ADJUSTABLE COUPLER
W/ 7K SET-BACK JACK**



14K Models

HD 12K SET-BACK JACK



16K Models



HD 4" Channel Ramps



10K Model Shown

SURE-TRAC DIFFERENCE

- HD 4" Channel Ramps
- Spring-Assist Ramps
- HD Slipper Spring Axle (14K Model)
- Sealed Brake Connections
- EverLink™ - High Performance Wiring Harness
- HD Bulkhead

FEATURES

- Pressure Treated 2 x 6 Decking
- Easy-Lube Hubs
- Radial Tires
- 2-5/16" Adjustable Coupler (14k Models)
- Set-Back Jack
- C-Channel Full Wrap Tongue
- HD Reinforced Tread Plate Fenders
- Rear Board Retainers
- Stake Pockets and Rub Rail
- (4) 1/2" D-Rings (10K & 14K Models)
- (4) 5/8" D-Rings (16K Models)
- Spare Tire Carrier
- 2' Beavertail
- 5' Stand Up Ramps
- Extended Tongue
- Powder Coat Finish

OPTIONS

- Coupler
- Jack
- Drop-In Toolbox
- Wheel Upgrades
- Color Options

[Contact Local Dealer For More Options](#)

SURE-TRAC

By Novae®

SMART - CONFIDENT - PROVEN

IMPLEMENT SPECIFICATIONS

		10K	14K	16k
GVWR		9900	14000	16000
GAWR		5200	7000	8000
Curb Weight	16'	2550	2800	3340
	18'	2750	2870	3520
	20'	2950	3195	3700
Payload	16'	7350	11200	12660
	18'	7150	11130	12480
	20'	6950	10805	12300
Frame		5" C-Channel	6" C-Channel	6" C-Channel
Cross Members		3" C-Channel (24" On-Center)		3" C-Channel (16" On-Center)
Tongue		5" C-Channel	6" C-Channel	8" C-Channel
Coupler		2-5/16" Ball	Adjustable 2-5/16"	Adjustable 4 Bolt Pintle
Jack		7K Dropleg, Set Back		HD 12K Dropleg, Set Back
Fenders		HD Double Brake Tread Plate		
Easy Lube Axles		Easy Lube Cambered with Brakes		Easy Lube Cambered with 3-3/8" Brakes
Suspension		Eye to Eye Spring	Slipper Spring	Slipper Spring
Tires		225/75R15 LRD	235/80R16 LRE	215/75R17.5 LRH
Wheels		15", 6 on 5.5, Radial	16", 8 on 6.5, Radial	17.5", 8 on 6.5, Radial
Decking		2 x 6 Pressure Treated Pine		
Lights		All LED Lights		
Electric Plug		7 Pole RV Molded Flat Blade		
Finish		Powder Coated High Gloss Black		
Overall Length/Flat	16'	273"/168"		
	18'	297"/192"		
	20'	321"/216"		
Drop-Tail Length		26"	26"	26"
Bed Width		81"	81"	81"
Deck Height		24"	24"	24"
Coupler Height		18"	Adjustable 19" - 27"	
Ramps		HD 4" C-Channel		

