

SPARE TIRE CARRIER



ENCLOSED WIRING







Set-Back Jack

SURE-TRAC DIFFERENCE

Fold-Flat HD Ramp Gate with Handle Spring-Assist Ramp Gate Self-Retained Gate Pins Zinc-Plated Set-Back Jack **Enclosed Wiring** 2 x 2 Tube Top Rail Tube Uprights

FEATURES

Pressure-Treated 2 x 6 Decking Easy-Lube Hubs 15" Radial Tire Sealed LED Lights Front and Rear Board Retainers Spare Tire Carrier Stake Pockets **HD Tread Plate Fenders** Powder Coat Finish

OPTIONS

Gate Upgrades Wheel Upgrades Color Options

Contact Your Local Dealer for More Options













SMART - CONFIDENT - PROVEN

TUBE TOP ATV SPECIFICATIONS

	6 x 12	7 x 12	7 x 14 SA	7 x 14 TA	7 x 16
GVWR (lbs)	2990	2990	2990	7000	7000
GAWR (lbs/axle)	3500	3500	3500	3500	3500
Curb Weight	1320	1370	1450	1740	1910
Payload	1670	1620	1540	5260	5090
Frame	3 x 2 x 3/16 Angle 3 x 2 x 1/4 Angle				4 Angle
Cross Members	3 x 2 x 3/16 Angle (24" On-Center)				
Top Rail	2 x 2 Square Tube				
Tongue	3" Channel (A-Frame) 4" Channel (A-Frame)				(A-Frame)
Uprights	2 x 2 Square Tube				
Coupler	2" Ball			2-5/16" Ball	
Jack	2K Zinc Plated, Set Back				
Fenders	Tread Plate, Square Rolled with Backer			Tread Plate, Double Brake with Backer	
Easy Lube Axles	Cambered Idler with Brake Flange			Cambered Brake (Both Axles)	
Suspension	Leaf Spring			Equalized Leaf Spring	
Tires	205/75R15 LRC				
Wheels	15", 5 on 4.5				
Decking	2 x 6 Pressure Treated Pine				
Lights	All LED Lights				
Electric Plug	4 Way Flat			7 Pole RV Molded Flat Blade	
Finish	Powder Coated High Gloss Black				
Overall Length	185"	185"	209"	209"	237
Bed Length	144"	144"	168"	168"	192"
Bed Width	71.5"	81.5"	81.5"	81.5"	81.5"
Deck Height	18"	18"	18"	18"	18"
Coupler Height	16"	16"	16"	16"	16"
Gate	2 x 2 Tube, Mesh Covered, Full Width Spring Assist Ramp Gate with Handle				







