# **HD LOW PROFILE DUMP SPECIFICATIONS**



#### **SPARE TIRE CARRIER**



#### STABILIZER JACK **RECEIVERS**



Jacks Optional





### **SURE-TRAC DIFFERENCE**

HD Combo Barn Door Spreader Gate with Cambar Integrated Side Body Stiffening System Integrated Tarp Mount Underbody Secure Tool Storage HD Ramps (Stored Underneath Bed) Slipper Springs Sealed Brake Connections

### **FEATURES**

 $\mathsf{EverLink}^{\scriptscriptstyle\mathsf{TM}} \operatorname{-} \mathsf{High} \operatorname{Performance} \operatorname{Wiring} \mathsf{Harness}$ Power Up, Power Down Hydraulics (Single Ram) Power Up, Gravity Down Hydraulics (Scissor and Telescopic) Deep Cycle Marine Grade Battery 110 Volt Battery Charger Easy-Lube Hubs **Radial Tires** Adjustable Coupler Set-Back Jack

Tongue Mounted HD Control Box with Key Lock All LED Lights 10 Gauge Floor **HD Treadplate Fenders** Side Steps (5) 1/2" D-Rings (12K & 14K Models) (5) 5/8" D-Rings (16K Models) Spare Tire Carrier Stake Pockets Stabilizer Jack Receivers (Jacks Optional) Powder Coat Finish

## **OPTIONS**

Tarp Kit Wheel Options **Color Options** 

All Wheel Brakes


**Contact Local Dealer For More Options** 













## SMART - CONFIDENT - PROVEN

## HD LOW PROFILE DUMP SPECIFICATIONS

		82" x 12	82" x 14	82" x 16	82" x 14	82" x 16	
GVWR (lbs)		12000	14000	14000	16000	16000	
GAWR (lbs/axle)		6000	7000	7000	8000	8000	
Curb Weight	Dual Ram	3240	3600	3960	N/A	N/A	
	Scissor	3400	3800	4160	4040	4360	
	Telescopic	3240	3600	4100	4540	5040	
Payload	Dual Ram	8760	10400	10040	N/A	N/A	
	Scissor	8600	10200	9840	11960	11640	
	Telescopic	8760	10400	9900	11460	10960	
Frame		5 x 2 Tube (Tele - 6x2, 3/16" Tube)	6 x 2, 3/16" Tube		6 x 2, 1/4" Tube		
Cross Members		4" C-Channel					
Tongue		6 x 2 Tube	6 x 2 Tube	6 x 2 Tube	8 x 2 Tube	8 x 2 Tube	
Sides		24"					
Coupler		Adjustable 2-5/16"			Adjustable 4 Bolt Pintle		
Jack			7K Dropleg, Set Back HD 12K Dropleg, Set Back			leg, Set Back	
Fenders		Heavy Duty Tread Plate, Double Brake					
Easy Lube Axles		Easy Lube Cambered Brake					
Suspension		Slipper Spring					
Tires		235/80R16 LRE 215/75R17.5 LRH				17.5 LRH	
Wheels			16", 8 on 6.5, Radial 17.5", 8 on 6.5, Radial				
Decking		10 ga. Smooth Steel					
Lights		All LED Lights					
Electric Plug		7 Pole RV Molded Flat Blade					
Finish		Powder Coated High Gloss Black					
Overall Length		198"	222"	246"	222"	246"	
Bed Length Inside		144"	168"	192"	168"	192"	
Bed Width Inside		82"	82"	82"	82"	82"	
Bed Height Inside		24	24"	24"	24"	24"	
Deck Height		29"	29"	29"	29"	29"	
Coupler Height		Adjustable 19-27"					
Gate		Combination Barn Door Spreader Gate with Cambar					
Hydraulic Hoist	Dual Ram	Dual Ram, Power Up, Power Down					
	Scissor	Power Up, Gravity Down					
	Telescopic	Power Up, Gravity Down					
Pump		3200 PSI 12VDC With Hydraulic Reservoir					
Battery		Group 24 Deep Cycle					









