

TILT BED CAR HAULER SPECIFICATIONS

SPARE TIRE CARRIER



Removable Fender
(Driver's Side)



Power Tilt Model Shown

SURE-TRAC DIFFERENCE

- HD Bulkhead
- Removable Fender (Driver's Side)
- Sealed LED Lights
- Sealed Brake Connections

FEATURES

- Pressure-Treated 2 x 6 Decking
- Easy-Lube Hubs
- 15" Radial Tires
- Silver Spoke Wheels
- 7K Dropleg Jack
- Full Wrapped Tongue
- Stake Pockets and Rub Rail
- (4) 1/2" D-Rings
- Spare Tire Carrier
- Powder Coat Finish

OPTIONS

- Coupler Upgrades
- Wheel Upgrades
- Color Options

[Contact Local Dealer For More Options](#)



SURE-TRAC

By Novae®

SMART - CONFIDENT - PROVEN

TILT BED CAR HAULER SPECIFICATIONS

	7 x 18 (Manual)	7 x 20 (Manual)	7 x 18 (Manual)	7 x 18 (Power)	7 x 20 (Manual)	7 x 20 (Power)
GVWR (lbs)	7000	7000	9900	9900	9900	9900
GAWR (lbs/axle)	3500	3500	5000	5000	5000	5000
Curb Weight	2110	2190	2180	2210	2250	2260
Payload	4890	4810	7720	7690	7650	7640
Frame	5" Tube					
Cross Members	3" C-Channel					
Tongue	5" Tube					
Coupler	2-5/16" Ball					
Jack	7K Dropleg, Set Back					
Fenders	Tread Plate, Double Brake with Backer, Driver's Side Removable					
Easy Lube Axles	Cambered Brake Both Axles					
Suspension	Double Eye Leaf Spring					
Tires	205/75R15 LRC	205/75R15 LRC	225/75R15 LRD	225/75R15 LRD	225/75R15 LRD	225/75R15 LRD
Wheels	15 in, 5 on 4.5	15 in, 5 on 4.5	15 in, 6 on 5.5	15 in, 6 on 5.5	15 in, 6 on 5.5	15 in, 6 on 5.5
Decking	2 x 6 Pressure Treated Pine					
Lights	All LED Lights					
Electric Plug	7 Pole RV Molded Flat Blade					
Finish	Powder Coated High Gloss Black					
Overall Length	278"	302"	278"	278"	302"	302"
Bed Length Flat	216"	240"	216"	216"	240"	240"
Bed Width	82"	82"	82"	82"	82"	82"
Deck Height	22.5"	22.5"	22.5"	22.5"	22.5"	22.5"
Coupler Height	17"	17"	17"	17"	17"	17"
Tilt Mechanism	Manual / Hydraulic			Electric / Hydraulic	Manual / Hydraulic	Electric / Hydraulic
Tilt Angle	14 Deg.	12 Deg	14 Deg	14 Deg	12 Deg	12 Deg

