


HD LOW PROFILE BEAVERTAIL DECKOVER SPECIFICATIONS

**SURE-TRAC**  
By Novae

HD STAKE POCKETS, RUB  
RAIL, AND CHAIN SPOOL



TUBE CONSTRUCTED  
BUMPER



Shown with Optional Heavy-Duty I-Beam Gooseneck



UNIVERSAL FULL-WIDTH RAMPS



OPTIONAL



SURE-TRAC DIFFERENCE

- Pierced I-Beam Frame
- Everlink™ - High Performance Wiring Harness
- Sealed Brake Connections

FEATURES

- Pressure Treated 2 x 6 Decking
- Oil Filled Hubs (Tandem Dual)
- Slipper Springs
- Radial Tires
- HD 12K Dropleg Jack
- Tube Constructed Bumper
- Spare Tire Carrier
- HD Stake Pockets and Rub Rail
- (10) 5/8" D-Rings
- Chain Spools
- Side Steps
- HD Bulkhead
- All LED Lights
- Powder Coat Finish

OPTIONS

- Gooseneck
- Ramps
- Oak Decking
- Spare Tire
- Color Options

Contact Your Local Dealer for More Options



**SMART - CONFIDENT - PROVEN**

## HD LOW PROFILE BEAVERTAIL DECKOVER SPECIFICATIONS

		8.5 X 20 + 5				
GVWR (lbs)		15000	17600	22500	25900	32000
GAWR (lbs/axle)		7000	8000	10000	12000	16000
Curb Weight	Bumper Pull	4640	4740	5540	5840	6210
	Gooseneck	4930	5030	5800	6100	6520
Payload	Bumper Pull	10360	12860	16960	20060	25790
	Gooseneck	10070	12570	16700	19800	25480
Main Frame		W12 x 14#/ft., I-Beam		W12 x 14#/ft., I-Beam		
Side Rails		5" C-Channel	6" C-Channel			
Cross Members		3" C-Channel (16" On-Center)				
Beaver Tail		Self-Cleaning Cleats				
Coupler	Bumper Pull	Adjustable Pintle	Adjustable 4 Bolt Pintle			
	Gooseneck	Adjustable 2-5/16"				
Jack	Bumper Pull	HD 12K Dropleg				
	Gooseneck	Dual HD 12K Jacks with Toolbox				
Axles		E-Z Lube Electric Brake		Oil Bath Bearing	E-Z Lube Electric Brake	Oil Bath Bearing
Suspension		Slipper Spring				
Tires		235/80R16 LRE	215/75R17.5 LRH	235/80R16 LRE		
Wheels		16", 8 on 6.5, Radial	17.5", 8 on 6.5, Radial	16", 8 on 6.5, Radial		
Decking		2" Pressure Treated Pine				
Lights		All LED Lights				
Electric Plug		7 Pole RV Molded Flat Blade				
Finish		Powder Coated High Gloss Black				
Overall Length	Bumper Pull	378"	378"	378"	378"	378"
	Gooseneck	426"	426"	426"	426"	426"
Deck Height		32"	32"	32"	32"	32"
Coupler Height	Bumper Pull	Adjustable 21"-29"				
	Gooseneck	Adjustable 31" - 39.75"				
Ramps		HD Fabricated Fold Flat with Double Hinged spring assist				

